

Ressources AriettaG25

GPIO		UART		I ² C																																																											
SPI		A/D		PWM & I ² S																																																											
Debug		USB WiFi																																																													
	<table border="1"> <thead> <tr> <th>Pin #</th> <th>Signal</th> <th>Dir</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>DP.1</td> <td>3V3 power out</td> <td>OUT</td> <td>Output from the internal regulator from 5 to 3.3 volt</td> </tr> <tr> <td>DP.2</td> <td>EN5V input</td> <td>INP</td> <td>If low turn off internal regulator from 5 to 3.3 volt</td> </tr> <tr> <td>DP.3</td> <td>DTXD</td> <td>OUT</td> <td>Debug port serial output at 115200,N,8,1 3V3 level</td> </tr> <tr> <td>DP.4</td> <td>DRXD</td> <td>INP</td> <td>Debug port serial input</td> </tr> <tr> <td>DP.5</td> <td>WAKUP</td> <td>INP</td> <td>Atmel MPU wakeup signal</td> </tr> <tr> <td>DP.6</td> <td>GND</td> <td></td> <td>Signal ground</td> </tr> </tbody> </table>	Pin #	Signal	Dir	Description	DP.1	3V3 power out	OUT	Output from the internal regulator from 5 to 3.3 volt	DP.2	EN5V input	INP	If low turn off internal regulator from 5 to 3.3 volt	DP.3	DTXD	OUT	Debug port serial output at 115200,N,8,1 3V3 level	DP.4	DRXD	INP	Debug port serial input	DP.5	WAKUP	INP	Atmel MPU wakeup signal	DP.6	GND		Signal ground		<table border="1"> <thead> <tr> <th>Pin #</th> <th>Signal</th> <th>Dir</th> <th>Description</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>WiFi TXEN</td> <td>OUT</td> <td>RF on/off control. Low level activated to off. Wired to PC30</td> </tr> <tr> <td>2</td> <td>LED</td> <td>N.C.</td> <td>WiFi module activity led. Not used</td> </tr> <tr> <td>3</td> <td>GND</td> <td></td> <td>Signal ground GND</td> </tr> <tr> <td>4</td> <td>USB B D-</td> <td></td> <td>USB Host B D-</td> </tr> <tr> <td>5</td> <td>USB B D+</td> <td></td> <td>USB Host B D+</td> </tr> <tr> <td>6</td> <td>VCC 3.3V DC</td> <td>OUT</td> <td>Output from the internal regulator from 5 to 3.3 volt</td> </tr> <tr> <td>7</td> <td>WPS</td> <td>OUT</td> <td>WSP function. Low level activated. Wired to PC16</td> </tr> </tbody> </table>	Pin #	Signal	Dir	Description	1	WiFi TXEN	OUT	RF on/off control. Low level activated to off. Wired to PC30	2	LED	N.C.	WiFi module activity led. Not used	3	GND		Signal ground GND	4	USB B D-		USB Host B D-	5	USB B D+		USB Host B D+	6	VCC 3.3V DC	OUT	Output from the internal regulator from 5 to 3.3 volt	7	WPS	OUT	WSP function. Low level activated. Wired to PC16
Pin #	Signal	Dir	Description																																																												
DP.1	3V3 power out	OUT	Output from the internal regulator from 5 to 3.3 volt																																																												
DP.2	EN5V input	INP	If low turn off internal regulator from 5 to 3.3 volt																																																												
DP.3	DTXD	OUT	Debug port serial output at 115200,N,8,1 3V3 level																																																												
DP.4	DRXD	INP	Debug port serial input																																																												
DP.5	WAKUP	INP	Atmel MPU wakeup signal																																																												
DP.6	GND		Signal ground																																																												
Pin #	Signal	Dir	Description																																																												
1	WiFi TXEN	OUT	RF on/off control. Low level activated to off. Wired to PC30																																																												
2	LED	N.C.	WiFi module activity led. Not used																																																												
3	GND		Signal ground GND																																																												
4	USB B D-		USB Host B D-																																																												
5	USB B D+		USB Host B D+																																																												
6	VCC 3.3V DC	OUT	Output from the internal regulator from 5 to 3.3 volt																																																												
7	WPS	OUT	WSP function. Low level activated. Wired to PC16																																																												